

**evoke**<sup>®</sup>

**LAMINATE**

**Desert Valleys Collection  
TDS Sheet**



**Wadi  
47069**



**Ramlat  
47070**



**Bromo  
47071**



**Kalahari  
47072**



**Chalbi  
47073**



**Namib  
47074**



**Karoo  
47075**



**Thar  
47076**

### Trims & Transitions



**Quarter  
Round**



**End Cap**



**Stair Nose  
Overlap**



**Stair Nose  
Flush**



**T-Mold**



**Stair Qnose  
Square**



**Multi-Purpose  
Reducer**

## DESERT VALLEYS COLLECTION PRODUCT SPECIFICATIONS

Plank Size	1292 x 193mm / 7.5" x 50" (nominal)
Thickness	8mm
Edge	Painted Bevel
Surface Texture	Brushed
Installation Method	Click Together
Limited Warranties	5 year commercial / 30 year residential
Material Composition	HDF
Formaldehyde Compliance	TSCA Title VI Compliant/Conforme au titre VI de la TSCA: Complies with US and Canadian composite wood products formaldehyde emission regulations
Low Emitting Qualification	GREENGUARD Gold Certified, CA Section 01350 Compliant
Environmental Product Declaration	EPD created as per ISO 14025 and EN 15804+A2 through the Institut Bauen und Umwelt e.V. (IBU)
Country of Manufacture	Germany

## PERFORMANCE SPECIFICATIONS

TYPE	STANDARD	DETAILS
Thermal Conductivity	EN 12667	0.12 W/(m*K)
Fire Classification	EN 13501-1	Cfl-s1
Slip Resistance	EN 13893	DS, ≥0.3
Antistatic Properties	EN 1815	yes, < 2kV
Abrasion Resistance	Test Method A, EN 13329, Annex E	AC4 / ≥4000 cycles
Impact Resistance	Small / Big Ball, EN 13329, Annex H	≥ 35mm ≥750 mm
Resistance to staining	EN 438 - 2	Group 1 + 2: Level 5, Group 3: Level 4
Thickness swelling	ISO 24336	≤ 18%
NALFA 24 Test	ANSI/NALFA LF-01	Pass
Static Indentation by constant pressure	ISO 24343-1	≤0.05mm
Effect of furniture leg	EN 424 (foot type 0)	No change in appearance or damage
Effect of castor chair	EN 425	25,000 cycles
Profile strength lengthways / crossways	ISO 24334	≥ 1.0 kN/m ≥2.0 kN/m
Joint tightness	ISO 4760	No water leakage after 24 hours of water exposure
Dimensional Tolerance of the board	ISO 24337	Length ± 0.5mm Width ± 0.1mm Thickness ± 0.5mm

## PACKING SPECIFICATIONS

SQUARE FEET PER BOX	PLANKS PER BOX	PATTERN REPEAT	BOXES PER PALLET
21.47	8	10	60