

**evoke<sup>®</sup>**

**LUXURY VINYL**

**City Block Collection  
TDS Sheet**



**Bakery  
45703**



**Bank  
45704**



**Park  
45705**



**Florist  
45706**



**Fountain  
45707**



**Hotel  
45708**



**Cathedral  
45709**



**Courtyard  
45710**

### Trims & Transitions



**Quarter  
Round**



**Stair Q Nose - Flush**



**Multi-purpose Reducer**



**V-SN-01**

## CITY BLOCK COLLECTION PRODUCT SPECIFICATIONS

| TYPE                   | STANDARD                  | DETAILS  |
|------------------------|---------------------------|--|
| Plank Size             |                           | 7" x 48"   |
| Thickness              | ASTM F386                 | 3.5mm (2.5mm LVT + 1mm IXPE)   |
| Wear layer             | ASTM F410                 | 12 mil   |
| Finish                 |                           | Diamante Shield™   |
| Edge                   |                           | Square   |
| Surface Texture        |                           | Brushed Embossing  |
| Installation Method    |                           | Glue Down Vinyl Plank  |
| Limited Warranties     | Commercial<br>Residential | 15 year Light<br>25 year   |
| Certifications         | GREENGUARD Gold           | Certified as Low-Emitting Material, CA Section 01350 compliant                     |
| Material Composition   |                           | 100% Virgin content, free of any added Ortho Phthalates or Heavy Metal Stabilizers |
| Country of Manufacture |                           | South Korea  |

## PERFORMANCE SPECIFICATIONS

| TYPE                  | STANDARD    | DETAILS                       |
|-----------------------|-------------|-------------------------------|
| Classification        | ASTM F1700  | Class III, Type B Vinyl Plank |
| Size & Squareness     | ASTM F 2055 | Passes                        |
| Chemical Resistance   | ASTM F 925  | Passes                        |
| Dimensional Stability | ASTM F 2199 | Passes                        |
| Resistance to Heat    | ASTM F 1514 | Passes                        |
| Resistance to Light   | ASTM F 1515 | Passes                        |
| Flexibility           | ASTM F 137  | Passes                        |
| Critical Radiant Flux | ASTM E 648  | Class I                       |
| Smoke Density         | ASTM E 662  | Passes                        |
| Slip Resistance       | ASTM D 2047 | Passes                        |
| Static Load Limit     | ASTM F 970  | Passes                        |
| IIC Sound Rating      | ASTM E 492  | 58                            |
| STC Sound Rating      | ASTM E 90   | 57                            |
| Delta IIC             | ASTM E 2179 | 23                            |

\*Sound testing was done over a 8" concrete slab with no ceiling

## PACKING SPECIFICATIONS

| SQUARE FEET PER CARTON | PIECES PER CARTON | CARTONS PER PALLET | PALLETS PER CONTAINER | SF PER CONTAINER |
|------------------------|-------------------|--------------------|-----------------------|------------------|
| 32.67                  | 14                | 50                 | 20                    | 32, 670          |